

AM 4

Digital Multi-position Hot Plate Stirrer

Precision, Ease-of-Use and Versatility in Four
Independent Positions

velp[®]

Driven by curiosity



Multi-position

- Four independent positions able to stir up to 1500 rpm, up to 15 L
- The 135 mm diameter aluminum alloy top plates ensure great temperature homogeneity and optimum heat transfer across the entire surface
- Two illuminated indicators always inform the operator when heating is on and temperature above 50°C
- Brushless motor ensuring power and resistance over time
- Brushless motor ensuring power and resistance over time
- Designed for the longest lifespan and guaranteed by 3 years warranty with online product registration



Instrument - Codes

AM4

230 V / 50-60 Hz

F20500590

Technical Data

| | |
|--------------------------|---|
| User interface | Analog |
| Housing material | Epoxy painted aluminum structure |
| Number of positions | Four positions |
| Plate material | Aluminum alloy |
| Plate diameter | 135 mm |
| Stirring volume | 15 L |
| Stirring speed range | 100 - 1500 rpm |
| Speed control | Analog |
| Motor | Brushless |
| Torque compensation | Speedservo™ |
| Temperature range | Room temp - 310 °c |
| Heating control | Analog |
| Hot plate warning system | Illuminated icons (when the temperature is above 50 °c) |
| Protection class | IP 42 |
| Power input | 2550 w |
| Weight | 5,8 kg (12.8 lb) |
| Dimensions (WxHxD) | 715x90x270 mm (28.1x3.5x10.6 in) |



Headquarters
Velp Scientifica Srl
Via Stazione 16
20865 Usmate (MB)
Italia
T +39 039 628811
velpitalia@velp.com

India
velpindia@velp.com

USA
Velp Scientific Inc
40, Burt Drive, Unit #1,
Deer Park
NY 11729 - U.S.
T +1 631 573 6002
velpusa@velp.com

LATAM
velplatam@velp.com

China
Velp China Co. Ltd.
Room 828, Building 1, No.778
Jinji Road, Pudong New Area,
Shanghai, China
Tel. +8621 34500630
velpchina@velp.com

SEA & Pacific
velpsea@velp.com

Velp Official Partner

Rev 4.10.2025

