

RC 2

Heating Plates

Safety, ease-of-use, and excellent heating in two independent positions.

velp[®]

Driven by curiosity



Practical and Easy to use

- Excellent Heating Performance
- Two independent positions able to heat the medium up to 310 °C
- The 135 mm diameter aluminum alloy top plate ensures great temperature homogeneity and optimum heat transfer across the entire surface
- Two illuminated indicators always inform the operator when heating is on and temperature above 50°C
- Different combinations of AluBlocks™ are accepted to maximize temperature control and save handling time
- Designed for the longest lifespan and guaranteed by 3 years warranty with online product registration



Instrument - Codes

RC 2	230 V / 50-60 Hz	F20700620
RC 2	115 V / 60 Hz	F20710620

Technical Data

User interface	Analog
Housing material	Epoxy painted aluminum structure
Number of positions	Two positions
Plate material	Aluminum alloy
Plate diameter	135 mm
Temperature range	Room temp. - 310 °c
Hot top warning system	Analog
Heating control	Illuminated Icons (when the temperature is above 50 °C)
Power input	1200 W
Weight	2.6 kg (5.8 lb)
Dimensions (WxHxD)	340x90x270 (13.4x3.5x10.6 in)



Headquarters
Velp Scientifica Srl
Via Stazione 16
20865 Usmate (MB)
Italia
T +39 039 628811
velpitalia@velp.com

LATAM
velplatam@velp.com

USA
Velp Scientific Inc
40, Burt Drive, Unit #1,
Deer Park
NY 11729 - U.S.
T +1 631 573 6002
velpusa@velp.com

SEA & Pacific
velpsea@velp.com

China
Velp China Co. Ltd.
Room 828, Building 1,
778 Jinji Road, Pudong,
Shanghai, China
Tel. +8621 34500630
velpchina@velp.com

India
Velp India Pvt. Ltd.
Office 323-324, Building 2
Raheja Tesla, MIDC, Turbhe,
400705, Navi Mumbai, India
velpindia@velp.com

Velp Official Partner

Rev 3.02.2026

